

C4212 Log Data Report

Borehole Information:

Borehole: C4212		Site: 216-U-1 and U-2 Cribs			
Coordinates (WA State Plane)		GWL (ft)¹: Dry	GWL Date: 02/24/2004		
North	East	Drill Date	TOC² Elevation	Total Depth (ft)	Type
Not Available	Not Available	Feb. 2004	Not Available	50	Push Hole

Casing Information:

Casing Type	Stickup (ft)	Outer Diameter (in.)	Inside Diameter (in.)	Thickness (in.)	Top (ft)	Bottom (ft)
Threaded steel	0.5	7 1/16	6 1/16	1/2	0.5	50
Outside and inside casing diameters were measured using a caliper and a steel tape. The measurements were rounded to the nearest 1/16 in.						

Borehole Notes:

This push-hole is located along the north side of the crib. Using an acoustic depth device, depth-to-bottom measured 49.6 ft from top-of-casing. Zero reference is the ground surface.

Logging Equipment Information:

Logging System:	Gamma 1E	Type:	SGLS (70%) 34TP40587A
Calibration Date:	01/2004	Calibration Reference:	GJO-2004-568-TAC
		Logging Procedure:	MAC-HGLP 1.6.5, Rev. 0

Spectral Gamma Logging System (SGLS) Log Run Information:

Log Run	1	2	3 / Repeat		
Date	02/26/04	02/26/04	02/26/04		
Logging Engineer	Spatz	Spatz	Spatz		
Start Depth (ft)	48.58	48.5	15.5		
Finish Depth (ft)	48.58	0.5	10.5		
Count Time (sec)	100	100	100		
Live/Real	R	R	R		
Shield (Y/N)	N	N	N		
MSA Interval (ft)	N/A	1.0	1.0		
ft/min	N/A ³	N/A	N/A		
Pre-Verification	AE093CAB	AE093CAB	AE093CAB		
Start File	AE094000	AE094001	AE094050		
Finish File	AE094000	AE094049	AE094055		
Post-Verification	AE095CAA	AE095CAA	AE095CAA		
Depth Return	N/A	0	0		

Log Run	1	2	3 / Repeat		
Error (in.)					
Comments	Sonde tip is just touching bottom of borehole.	No fine-gain adjustment.	Repeat section.		

Logging Operation Notes:

Zero reference was ground surface. Logging was performed with a centralizer installed on the sonde. Pre- and post-survey verification measurements for the SGLS employed the Amersham KUT (^{40}K , ^{238}U , and ^{232}Th) verifier with serial number 118.

Analysis Notes:

Analyst:	Sobczyk	Date:	3/04/04	Reference:	GJO-HGLP 1.6.3, Rev. 0
-----------------	---------	--------------	---------	-------------------	------------------------

SGLS pre-run and post-run verification spectra were collected at the beginning and end of the day. All of the verification spectra were within the acceptance criteria. The peak counts per second (cps) at the 609-keV, 1461-keV, and 2615-keV photopeaks on the post-run verification spectrum as compared to the pre-run verification spectrum for the day were between 1.9 percent lower and 7.1 percent higher at the end of the day. Examinations of spectra indicate that the detector functioned normally during logging.

Log spectra were processed in batch mode using APTEC SUPERVISOR to identify individual energy peaks and determine count rates. Verification spectrum was used to determine the energy and resolution calibration for processing the data using APTEC SUPERVISOR. Concentrations were calculated in EXCEL (source file: G1EJan04.xls). Zero reference was the ground surface. Based on the field measurements, the casing configuration was assumed as one string of 6-in. casing with a thickness of 1/2 in. to 48.58 ft (total logging depth). Dead time and water corrections were not required.

Log Plot Notes:

Separate log plots are provided for gross gamma and dead time, naturally occurring radionuclides (^{40}K , ^{238}U , and ^{232}Th), and man-made radionuclides. Plots of the repeat logs versus the original logs are included. For each radionuclide, the energy value of the spectral peak used for quantification is indicated. Unless otherwise noted, all radionuclides are plotted in picocuries per gram (pCi/g). The open circles indicate the minimum detectable level (MDL) for each radionuclide. Error bars on each plot represent error associated with counting statistics only and do not include errors associated with the inverse efficiency function, dead time correction, or casing correction. These errors are discussed in the calibration report. A combination plot is also included to facilitate correlation. The ^{214}Bi peak at 1764 keV was used to determine the naturally occurring ^{238}U concentrations on the combination plot rather than the ^{214}Bi peak at 609 keV because it exhibited slightly higher net counts per second.

Results and Interpretations:

Man-made radionuclides were not detected in this borehole. The plots of the repeat logs demonstrate reasonable repeatability of the SGLS data for the natural radionuclides at energy levels of 609, 1461, 1764, and 2614 keV.


¹ GWL – groundwater level

² TOC – top of casing

³ N/A – not applicable

C4212

Man-Made Radionuclides




Zero Reference = Ground Surface


Date of Last Logging Run
2/26/2004

C4212


Natural Gamma Logs



C4212 Combination Plot




C4212 Combination Plot



C4212

Total Gamma & Dead Time



Zero Reference = Ground Surface
Date of Last Logging Run
2/26/2004

C4212

Rerun of Natural Gamma Logs (15.5 to 10.5 ft)

